

BUILT TO RESIST



APPLICATION

Mixers, Agitators

The Var-Spe variator is used to drive the mixing shaft.

BENEFITS

- **Wide speed range 0-1500 rpm** on both the output directions (0-1750 rpm using 60Hz motor)
- **High torque** at low speed
- Available in **Atex version** for zone 1/21 and 2/22
- **Zeroing with motor on** ($n_1=1500$ rpm, $n_2=0$ rpm)
- **Speed preset with motor off**
- **Remote speed control:** 4-20mA, 0-10V, keypad, pneumatic
- **Adjustable torque limiter**



Pharmaceutical sector



Waste treatment



Oil&gas sector

BUILT TO RESIST



- HARD ENVIRONMENT
- LONG LIFE
- RELIABILITY

PRODUCT RANGE



K2 (0,37-0,55-0,75 kW)



K4 (1,1-1,5 kW)



K5 (2,2-3-4 kW)



15 (3-4 kW)



16 (5,5-7,5 kW) **16B** (11 kW)



17 (15 kW) **17B** (22 kW)



Ex ATEX

Atex-certified variators
(0,37-22 kW)

VAR-SPE SRL
Via Cordellina, 81 36077 Altavilla Vicentina (VI) Italia

Ph. +39 0444 572.011
Fax +39 0444 573.188

www.varspe.com
info@varspe.com